



- Electromechanical control panel.
- 2 washing cycle of 90°/180°.
- Tank capacity: 33 l./Heating power: 4.5 kW.
- Boiler capacity: 7 l./Heating power: 6.0 kW.
- Wash pump power: 0.75 kW.
- Rinsing consumption: 2.6 l/rinse.
- Upper and lower washing and rinsing arms.
- Stainless steel washing arms.
- Built-in rinse-aid dispenser.
- Anti backflow valve fitted.
- Tank filter in composite material.
- Single skin hood.
- Safety thermostat in washing tank and boiler.

- Temperature adjustment: wash 60 °C and rinse 85 °C.
- Multi-Voltage: 400 V 3N, 230 V 3~, 230 V 1N.
- Adjustable boiler heating power (Multi-Power).
- Accessories supplied: 1 basket CP-16/18, 1 basket CT-10 and 1 basket for cutlery CU-7.
- Continuous cycle until manual stop. Maximum duration 600 seconds.

OPTIONAL MODELS WITH

- Double skin hood.
- Built-in drain pump.
- Built-in electric rinse-aid dispenser.
- Built-in detergent dispenser.
- Wash tank stainless steel filter.
- Stainless steel rinsing arms.
- 60 Hz version.

Model	Reference	Baskets/hour	Door clearance (mm)	Dimensions (mm)	Detergent dispenser	Drain pump	Power (kW)	Voltage (V)
GEX-H500	19104672	40	440	630 x 750 x 1482	No	No	11.25	400V-3N-50Hz
GEX-H500 DD	19104673	40	440	630 x 750 x 1482	Yes	No	11.25	400V-3N-50Hz
GEX-H500 B	19104674	40	440	630 x 750 x 1482	No	Yes	11.25	400V-3N-50Hz
GEX-H500 B DD	19104675	40	440	630 x 750 x 1482	Yes	Yes	11.25	400V-3N-50Hz