

## R 45



**3**  
BLADES

**45 L**

<b>D</b>	Number of meals	200 à 1000 covers
	Quantity processed per operation	6 to 27 kg

### **A** SALES FEATURES

**Vertical Cutter Mixer R 45** is designed for processing both large and small quantities of meat, vegetables and smooth textured mousses, as well as for grinding and kneading foodstuffs in a minimum of time.

### **B** TECHNICAL FEATURES

Vertical Cutter Mixer R 45. Three-Phase. Power 9000 W. 2 speeds. 100% stainless-steel appliance with 3 built in legs. Control panel with flush buttons and digital timer from 0 to 15 minutes. Removable and tiltable 45L stainless-steel bowl. Bowl-base blade assembly with 3 detachable and height-adjustable smooth blades included. 200 to 1000 meals and more.

Select all the options at the back page, **F** part.

### **C** TECHNICAL DATA

<b>Output power</b>	9000 Watts	
<b>Electrical datas</b>	Three phase No plug included	
<b>Speeds</b>	50Hz : 1500 and 3000 rpm 60Hz : 1800 and 3600 rpm	
<b>Dimensions (LxWxH)</b>	760 x 600 x 1400 mm	
<b>Rate of recyclability</b>	95%	
<b>Net weight</b>	138 kg	
	<b>Supply</b>	<b>Amperage</b>
	400V/50/3	40 Amp*
	230V/50/3	63 Amp*
	220V/60/3	40 Amp*
	380V/60/3	63 Amp*
		<b>Reference</b>
		53331
		53335
		53333
		53334

**STANDARDS**  
NF EN 12100-1 & 2 - 2004, NF EN 60204-1 - 2006, NF EN 12852, NF EN 60529-2000



### **E** PRODUCT FEATURES/BENEFITS

#### **MOTOR BASE**

- Direct drive induction motor (no belt) for intensive use.
- Power 9000 Watts.
- 100% stainless-steel construction and three sturdy legs for total stability.
- Stainless steel motor shaft.
- IP65 control panel with flush buttons and digital timer.
- Magnetic safety and motor brake.
- **2 speeds : 1500 and 3000 rpm (50Hz) 1800 and 3600 rpm (60Hz).**
- Pulse function for a better cut precision.

#### **CUTTER FUNCTION**

- 45 litre bowl : **removable and tiltable at more than 90°c** for effortless emptying and cleaning.
- **Bowl-base blade assembly** with 3 detachable and height-adjustable blades to ensure a perfectly uniform consistency, even when processing small quantity.
- **Stainless-steel construction** for making cleaning easier.
- **Timer from 0 to 15 minutes** for a better preparation control.
- **Transparent lid** with lid wiper to enable user to monitor processing.
- **Opening in centre of lid** for adding liquid or dry ingredients during processing..

#### **INCLUDED ACCESSORIES**

- 3 stainless steel smooth blade assembly
- Lid wiper

## R 45

### F OPTIONS

- 3 coarse serrated blade assembly for grinding and kneading - Ref. 57082
- 3 fine serrated blade assembly for chopping herbs and spices - Ref. 57084
- Set of 3 retractable wheels - Ref. 57062



### \* N O T E

When the appliance is switched on, the current is several times greater than the nominal current.

“The switch-on current of appliances must be taken into account when determining the cross-section of the conductors and choosing the systems that protect against excess current, in order to avoid excessive voltage drops during the switch-on period and the untimely triggering of the protective device.”

We advise you to use a protective device specific to the switching-on of asynchronous motors. In every case, you must comply with the legislation currently in force.

### G

### DRAWINGS & DIMENSIONS

